# **VERSA-FAST FASTENER**

Gypsum, Cementitious Wood Fiber & Lightweight Insulation Concrete Roofing Fasteners

#### **DESCRIPTION**


The ASAP Fastener System Fasteners are engineered to secure insulation, cover boards and base sheets to lightweight insulating concrete (LWIC) and gypsum decks. The Versa-Fast Fastener features an exclusive thread design engineered for exceptional pullout. When used in conjunction with our Versa-Fast 3" Metal Plate, multiple fasteners can be installed to achieve the required minimum pullout.

#### **TYPICAL PROPERTIES\***

PROPERTY	VALUE		
Material	SAE C1022, heat treated		
Coating	Epoxy E-Coat		
Fastener Head	#2 Phillips Truss		
Tensile Strength	2,000 lbf		
Shear Strength	1357 lbf		
Corrosion Resistance	<15% Red rust after 30 cycles		

<sup>\*</sup> All values shown are nominal.

## **PRODUCT SPECIFICATION**



#### **PRODUCT SELECTION**

PART#	PART LENGTH		THREAD LENGTH		PACKAGING		QTY/
	Inches	мм	Inches	мм	QTY/Bucket	Weight (lb)	PALLET
VF-2250	2 1/4	57.2	1,000	54.0	1,000	19.0	80,000
VF-3250	2 1/4	82.55	1,000	54.0	1,000	20.0	80,000
VF-4250	2 1/4	107.5	1,000	54.0	1,000	33.0	80,000



Enlarged to show detail

### PERFORMANCE DATA

SUBSTRATE	DENSITY	YIELD STRENGTH	AVERAGE ULTIMATE PULLOUT*	
	pcf	psi	lb	
Aggregate LWIC	63	370	190	
Cellular LWIC	41	290	320	
Gypsum	93	340	350	

\*One fastener per plate

## **INSTALLATION**

**For LWIC and Gypsum Decks:** Using the #2 Phillips drive bit provided and a 0-1500 rpm screw gun, install the Versa-Fast Fastener and Metal Plate through the substrate and into the approved deck. The fastener must penetrate the deck a minimum of 2 inches. Care should be taken to orient the fastener perpendicular to the deck and not to overdrive the fastener to prevent damage to the cover board, insulation or membrane.

#### **PULLOUT TESTING**

The strength of different roof decks can vary widely and can be adversely affected by moisture and other conditions. Therefore, it is recommended that a fastener pull test be conducted to help evaluate deck condition and fastener suitability. Contact Performance Roof Systems Technical Services to schedule testing.

## **APPROVED ACCESSORIES**

Versa-Fast Metal Plate

